



# Thermatrans Plus<sup>TTP</sup>

Freezing Point °C	%v/v Thermatrans Plus <sup>TTP</sup>	Refractive Index (R.I.) @ 20°C
-10	26.7	1.3624
-15	35.1	1.3721
-20	41.4	1.3794
-25	46.3	1.3850
-30	50.4	1.3897
-35	54.2	1.3939
-40	57.7	1.3977

Thermatrans Plus<sup>TTP</sup> is a Mono Propylene Glycol (MPG) based high performance, multi-component, inhibited heat transfer fluid designed to harness and transfer naturally occurring heat in both ground and air source heat pumps.

The dilution rate depends on the freeze point required by the system. Please refer to our Thermatrans Technical Support Guide for further information.

Before installation of Thermatrans Plus<sup>TTP</sup>, we recommend that all systems must be cleaned, with all debris and deposits removed. Ideally, systems should be treated to prevent bacterial contamination. A system cleaning fluid is available from Kilfrost.

Whilst Thermatrans Plus<sup>TTP</sup> is fully inhibited, on dilution we recommend potable water as a minimum water source requirement.

The refractive index can be measured using a refractometer, which is available from Kilfrost.

With regards to miscibility with other manufacturers' fluids, please refer to the Thermatrans Technical Support Guide.

P102 Keep out of reach of children.

P103 Read label before use.

EUH210 Safety data sheet available on request.

BATCH NUMBER:



[www.kilfrost.com](http://www.kilfrost.com)

© 2013 Kilfrost Ltd Thermatrans is a trademark of Kilfrost Ltd in the EU  
Kilfrost Time Central, 32 Gallowgate, Newcastle upon Tyne, NE1 4SN UK



This product was manufactured in a plant whose quality management system is certified/registered as being in conformity with 9001

Version 3